

the MINI-BRUTE

Now you can control a full
40 to 80 Amps with a dash or
panel-mounted momentary-on,
pushbutton switch
for STARTER or CONTROL
applications!

And —it's COMPLETELY WATERPROOF



3 Inches
[Actual Size]

*Model 1085

...can't be done?

We bet \$105,000 in U.S. Government testing fees
and research that *Nartron* could do it. . .

—And we won!

HIGH PERFORMANCE — HIGH RELIABILITY

CERTIFIED TO MIL SPECS

Electrical

- 28 Volts D.C.
- 40 Amps Resistive, 60 Amps overload.**
- 1,000 Volt Minimum Dielectric Breakdown.
- 50 MV [max] Forward Voltage Drop at full 40 Amps.
- Extremely Reliable: 50,000 Cycles [min] at full rated load.

Mechanical

- Shock & Vibration proof to 50 G's imposed force.
- Terminal Strength: 40 pounds minimum.
- Completely Waterproof; withstands plus or minus 6 PSI.
- Corrosion, Dust and Fungus-proof.
- Total Weight: 3 ounces.

Operating

- Single-pole, Normally-Open, Momentary Snap Action.
- Force: 4—8 pounds operating.
- Pretravel: 0.060 (Minimum)
- Temperature Range: —67° to 185° Fahrenheit (Min. Range)

Terminals

- 0.185" Diameter Silver-Plated Male Tip (Bullets).
- Mating Terminal: Standard 15 Female (Barrel). Rubber Boot Shielded per MIL-R-3065.

Mounting

- 5/8 x 24 Mounting Nuts and Locking Washer.
- Fits Panels up to 0.800" thick.

**12 Volt Performance:
60—80 Amps.

One-Inch Diameter Function Indicator Buttons
with "ENGINE STOP," "ENGINE START,"
and other identifications available.

*Patents Pending

NARTRON
CORPORATION

"...we turn things on..."

REED CITY, MICHIGAN 49677

231 - 832-5525